

# SILO BAG MACHINE FOR DRY GRAIN MAIZCO EX III 9200



FOLLOWING WITH THE TASK OF SATISFYING ITS CUSTOMERS REQUIREMENTS, **MAIZCO** HAS DEVELOPED THIS NEW PRODUCT, ACHIEVING A TOP-QUALITY CONSTRUCTIVE, EASY TO OPERATE AND RELIABLE MACHINE.



# SILO BAG MACHINE FOR DRY GRAIN EX III9200



Once the bagging tasks are finished, through a simple and quick process, the wheels of the working axis are removed and placed in the transport axis so as to move the machine.

The brakes are set over the working axis and operate directly over the wheels. The transmission to the auger is made through a PTO shaft, 1" sprockets and ASA 80H roller chain.

During the operation, the height of the machine is regulated through an adjustable arm set over the working axis. The bag is easily loaded by a lifting winches and the perch.

The grain tank has about 1600 liters capacity and it is bolted to be easily removed if the transport conditions require it.

The auger of high working capacity at low rpm is set over spherical roller bearings. The auger tube extends inside the machine to minimize movements/damage of the grains inside the bag. The machine is provided with an extendable tongue for transport, which is hidden during bag loading operation. The bag-pressing flap pivots over bushings at the back and its height is regulated through a chain and an adjuster.

## TECHNICAL SPECIFICATIONS

Type of bag	9 Feet - 200 Tn	Rims	550 x 15"
Maximum bagging capacity	250 Tn/h	Tyres	LT 215 / 75 / R-15

Ruta nacional Nº 8 - km 411,060  
[x2624WCA] - Arias - Córdoba  
Tel: (03468) 440347 / 440330  
[www.maizco.com.ar](http://www.maizco.com.ar) | [ventas@maizco.com.ar](mailto:ventas@maizco.com.ar)

# **Maizco**